



ErgoDeck ESD

Group 557

Static electricity is created by two materials rubbing together, and seeks a path to ground – often through the human body or through sensitive, conductive equipment. The best way to eliminate these risks is to create a static-dissipative environment. ErgoDeck ESD - a comprehensive flooring solution - offers the best defense. Used over conductive sub-flooring, ErgoDeck ESD is your best defense against fatigue and static shock that could compromise the quality of your products. Made of a proprietary TPO/Carbon blend, the ESD properties are throughout the entire tile. **Must be used over conductive flooring.** Positive interlocks stay secure, ensuring areas of any size are protected When installed wall-to-wall, ramps and corners aren't necessary. For transition areas use ErgoDeck's standard, universal ramps.

NOTE: Wear a heel grounder (793-Heel)

- U.S. PATENT NO. D502,557; D520,650
- Standing relief in static sensitive applications
- EOS/ESD S7.1: $1 \times 10^6 - 1 \times 10^9$ (meets ANSI/ESD 20.20 requirements)
- Use over conductive floor
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- Carbon impregnated TPO tiles provide maximum durability
- Overall thickness 7/8"

Type Anti-Fatigue ESD Flooring

Suitable Environment Dry

Customization Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Solid

Compound Carbon impregnated TPO

Recycled >80%

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .65 / Wet: COF = .42
Compression Deflection	ASTM D575-91 / 4.84%
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: $1 \times 10^6 - 1 \times 10^9$ (meets ANSI/ESD 20.20 requirements)
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
557.78x18x18BK-CS10	715411003303	Black	0.875	18" x 18"	Y	CS-10

