



## ErgoDeck Heavy Duty Solid

### Group 562

A dependable, ergonomic floor that will withstand heavy use. The patented LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 15 cm (6") wide safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck Heavy Duty is the best choice in areas with heavy cart and foot traffic. Why? The firmer compound lets carts roll over the tiles with ease. Meanwhile, the underside box-spring design provides structural support and impact absorption for health and productivity, even in multi-shift operations.

- Standing relief in wet or dry applications
- Customise in 8 cm (3") increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version and with GRITSHIELD for extra traction
- Overall thickness 22 mm (7/8")

|                             |   |
|-----------------------------|---|
| <b>Type</b>                 | Anti-Fatigue Flooring                   |
| <b>Suitable Environment</b> | Dry, Wet, Oily                          |
| <b>Customisation Level</b>  | C3 - Full Custom (Length, Width, Shape) |
| <b>Solid Drainage</b>       | Drainage                                |
| <b>Compound</b>             | PVC                                     |
| <b>Recycled</b>             | >80%                                    |
| <b>Warranty</b>             | 3 Years                                 |

| Property                | Test / Result                                |
|-------------------------|--|
| Flammability            | MVSS 302 / 'A'; Rating                       |
| Tabor Abrasion          | ASTM D 3884 / 1% loss                        |
| Temperature Range       | -17 to 49_ Celsius                           |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .65 / Wet: COF = .42 |
| Compression Deflection  | ASTM D575-91 / 4.84%                         |
| Tear Strength           | Not Available                                |
| ESD Rating              | Not Available                                |
| Dielectric Strength     | Not Available                                |

| Part Number         | UPC          | Colour | Thickness | Dimensions | Stock Part | UOM   |
|---------------------|--------------|--------|-----------|------------|------------|-------|
| 562.78x18x18BK-CS10 | 715411570072 | Black  | 7/8       | 46 x 46    | Y          | CS-10 |
| 562.78x18x18BK      | 715411570089 | Black  | 7/8       | 46 x 46    | N          | EA    |
| 562.78x18x18BL      | 715411058013 | Blue   | 7/8       | 18 x 18    | N          | EA    |
| 562.78x18x18BL-CS10 | 715411191208 | Blue   | 7/8       | 46 x 46    | N          | CS-10 |

|                |              |        |     |         |   |    |
|----------------|--------------|--------|-----|---------|---|----|
| 562.78x18x18GN | 715411058112 | Green  | 7/8 | 18 x 18 | N | EA |
| 562.78x18x18YL | 715411458202 | Yellow | 7/8 | 18 x 18 | N | EA |