



ErgoDeck® General Purpose Open with Gritshield®

Group 565

A high traction, ergonomic floor that will withstand heavy use. The LockSafe Positive Interlocking System™ delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and re-positioned as work centers change to fit customer needs. The optional 6" (15 cm) side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck General Purpose with GRITSHIELD™ increases traction by 40% and addresses worker health and safety in areas with primarily foot traffic and light cart traffic.

- U.S. PATENT NO. D502,557; D520,650
- Softer compound for greater standing relief in wet or dry applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version and with GRITSHIELD for extra traction
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Type Anti-Fatigue Flooring

Suitable Environment Wet, Oily, Slippery

Customization Level C3 - Full Custom (Length, Width, Shape)

Solid or Drainage Drainage

Compound PVC

Recycled >80%

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTMASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
565.78x18x18CH	715411059515	Charcoal	0.875	18" x 18"	Y	EA
565.78x18x18CH-CS10	715411060818	Charcoal	0.875	18" x 18"	Y	CS-10