



## ErgoDeck® General Purpose Solid with Gritshield®

### Group 567

A high traction, ergonomic floor that will withstand heavy use. The LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. ErgoDeck General Purpose with GRITSHIELD increases traction by 40% and addresses worker health and comfort in areas with primarily foot traffic and light cart traffic.

- U.S. PATENT NO. D502,557; D520,650
- Softer compound for greater standing relief in wet or dry applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version and with GRITSHIELD for extra traction
- Overall thickness 7/8"

<b>Type</b>	Anti-Fatigue Flooring
<b>Suitable Environment</b>	Wet, Oily, Slippery
<b>Customization Level</b>	C3 - Full Custom (Length, Width, Shape)
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	PVC
<b>Recycled</b>	>80%

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTMASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
567.78x18x18CH	715411061617	Charcoal	0.875	18" x 18"	Y	EA
567.78x18x18CH-CS10	715411060023	Charcoal	0.875	18" x 18"	Y	CS-10