



ErgoDeck® Heavy Duty Solid with Gritshield®

Group 563

A slip-resistant ergonomic floor that will withstand heavy use. The LockSafe Positive Interlocking System delivers secure connections. Perfect for lean manufacturing, tiles can be unlocked and repositioned as work centers change to fit customer needs. The optional 6" side safety ramps and corners have countersunk holes for semi-permanent installation. Available in a solid and drainage version, ErgoDeck Heavy-Duty with GRITSHIELD delivers 40% more traction and withstands heavy use and cart traffic.

- U.S. PATENT NO. D502,557; D520,650
- Secure footing in slippery applications
- Customize in 3" increments to fit any area or configuration
- Positive Interlocking System prevents separation
- Easily replace single pieces or sections as needed to reduce costs
- 100% Silicone Free PVC tiles provide maximum durability
- Available in Solid and Drainage version
- Overall thickness 7/8" (22 mm)
- Each case covers 22.5 sq. feet (2.2 sq. meters)

Type	Anti-Fatigue Flooring
Suitable Environment	Wet, Oily, Slippery
Customization Level	C3 - Full Custom (Length, Width, Shape)
Solid or Drainage	Solid
Compound	PVC
Recycled	>80%
Warranty	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTMASTM D 3884 / 1% loss
Temperature Range	0 to 120 F
Coefficient of Friction	ASTM F1677-05 / Dry: COF = 1.1 / Wet: COF = .93
Compression Deflection	Not Available
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
563.78x18x18BK	715411570911	Black	0.875	18" x 18"	Y	EA
563.78x18x18BK-CS10	715411570904	Black	0.875	18" x 18"	Y	CS-10